

# PLASTI 635

## SINGLE/DOUBLE SIDE ROLL LAMINATOR

Reel laminator with hot rollers to be used both for single or double side lamination jobs. **1000mt OPP film** rolls can be installed on the upper reel holder so to save money on purchase of bigger rolls.

Special features are: **independent control of heating** on both rolls so to preserve back print in case of single side lamination, adjustable film tension with side clutch, **long lasting silicone rollers** for better heat distribution, IR **contact-less temperature sensors** measure the actual temperature on top and bottom roller for more accurate temperature set, **made in Italy PCB** integrated with **MSC® Interface**.

**Profit calculation** is made easier with PLASTI 330 thanks to the actual **film consumption** monitoring for each single laminating job.

Reels with internal mandrel of mm 25, 57 or 75 can be used on the machine thanks to adaptors. 25mm and 75mm core adaptors are included.

Optional micro-perforator on top lamination film can be installed in order to facilitate manual separation of OPP single side laminated sheets.



**MSC® Interface**

**LAMINATION & ENCAPSULATION**

**OPTIONAL STAND**

**SILICON ROLLERS**

**LAMINATION COST CONTROL**



MSC Interface on  
Roll laminator PLASTI 330

### MSC® Interface: a mix of innovation

- 1 MSC Interface:** easy control on all lamination process with one single knob and a very intuitive software
- 2 Contact-less sensor** as part of MSC Interface reads the temperature directly on laminating roller's surface for accurate reading and quick adjustment
- 3 Made in Italy PCB,** and european quality components ensure high reliability and useful features like film consumption report for each job for accurate cost calculation

### MADE IN ITALY



Mamo Smart Control Interface integrates made in Italy PCB and European quality components for top reliability.

### EASY CONTROL



Fast set up and machine control through one single knob and very intuitive display.

### PROFIT CALCULATION



Calculate exact material consumption and production quantity in order to obtain net material cost for each single job.

### OPTIONAL STAND



For single side lamination jobs just keep on feeding the sheets overlapping them and than separate them by hand saving a lot of time on trimming operations.

### TECHNICAL SPECIFICATIONS:

Maximum sheet width (mm)	665
Maximum lamination film width (mm)	635
Indipendent rollers heating	YES
Maximum speed (mt/min)	0 - 2
Laminating roller pressure	MECHANIC
Anti-curling bar for single side lamination	NO
Control system	MSC® Interface
Maximum temperature (°C)	170
Power consumption - requirement	1800W - 230V 50/60 Hz
Weight (kg)	38 (without stand)